

RADIFORM

Quality Certified Components

Product:

Heat Shrink – RBKE Adhesive Lined Break Outs

Applications:

Provides sealing of cable sheaths for power cable up to 1kV and telecommunication cables.
Acts as a breakout in multi core cables for branching prior to terminations.

General:

- Resistance to chemical, fuel oil, insulation oil, copper corrosion and fungus
- Hot melt adhesive for effective water and environmental sealing
- High tensile strength
- UV stabilised

Specifications:

Products conform and tested to IEC and ASTM

Product Technical Data		
Properties	Test Method	Typical value
Tensile strength	ASTM-D-2671	>13Mpa min.
Elongation at break	ASTM-D-2671	300%
Accelerated Aging	ASTM-D-2671	120°C 168hrs
Elongation break after Aging	ASTM-D-2671	>250%
Density	ASTM-D-792	1.05
Volume Resistance	IEC 93	10 ¹³ Ohm/cm

The above information corresponds to our actual knowledge and are according to our knowledge is rendered correct and reliable. But they do not represent binding properties. Customers and end-users need to decide autonomously about the application of the product in the provided range. Under no circumstances is Red2Go Pty Ltd liable for any eventual, indirect or consequential damages arising from the sales, resale, transfer, use or misuse of the product. Our Liabilities are limited to only in replacing products due to any unforeseen specification variance.